

## Carbon-14 release from irradiated stainless steel

E. de Visser – Týnová<sup>1</sup>, S.W. Swanton<sup>2</sup>, S.J. Williams<sup>3</sup>, M.P. Stijkel<sup>1</sup>, A.J. Walker<sup>4</sup>, R. Otlet<sup>4</sup>

<sup>1</sup> Research and Innovation, Nuclear Research and consultancy Group, Westerduinweg 3, 1755 LE Petten – The Netherlands

<sup>2</sup> Wood, Building 150, Thomson Avenue, Harwell Campus, Didcot, OX11 0QB, United Kingdom

<sup>3</sup> Radioactive Waste Management, Building 587, Curie Avenue, Harwell Campus, Didcot, OX11 0RH, United Kingdom

<sup>4</sup> RCD Lockinge, RCD Lockinge Ltd, Unit 1 Lockinge Stables, East Lockinge, Wantage, OX12 8QY, United Kingdom

Carbon-14 (half-life 5,730 years) is a key radionuclide in the assessment of the safety of a geological disposal facility (GDF) for radioactive waste. In particular, the radiological impact of gaseous carbon-14 bearing species has been recognised as a potential issue. Carbon-14 is expected to be released from a GDF over a timescale of several thousand years. A number of radioactive gases will be generated from waste materials within a GDF, with carbon-14 bearing methane ( $^{14}\text{CH}_4$ ) likely to dominate any carbon-14 transported in a gas phase, potentially reaching the biosphere at low activity concentrations. Sources of carbon-14 include irradiated graphite, irradiated steels and Zircalloys, irradiated reactive metals, spent ion-exchange resins and spent fuel.

The objective of this work is to measure the rate and speciation of carbon-14 release from irradiated stainless steel on leaching under high-pH anaerobic conditions, representative of a cement-based near field for intermediate- and some low-level wastes (ILW/LLW). In particular, this includes measurements of releases to the gas phase as well as to solution. The gas phase carbon-14 collection method allows for the discrimination of carbon-14 released as  $^{14}\text{CO}_2$ ,  $^{14}\text{CO}$  (and volatile oxidized species) or  $^{14}\text{C}$ -hydrocarbons. The carbon-14 solution analysis method used to date has measured the inorganic carbon-14 release only. Work is in progress to measure the total carbon-14 release to solution that includes any dissolved organic carbon-14 species. Three experiments have been in progress in NRG's Hot Cell Laboratory at Petten for a period of 20 months: two contain irradiated stainless steel with similar total inventories of carbon-14 (and also cobalt-60); the third is a control experiment with unirradiated stainless steel from the same batch. The steel samples are being leached in  $0.1 \text{ mol dm}^{-3}$  NaOH solution. The three experiments have been sampled six times to date and analytical data are now available for the carbon-14 releases to the gas phase, inorganic carbon-14 to solution and cobalt-60 releases to solution up to 13 months leaching. The experiments are still running and further sampling is planned after 2 years.

The presentation will cover: initial characterisation of irradiated steel samples to assess their suitability for use in the experiments; the approach selected and the conceptual design of the experiments for measuring carbon-14 releases from irradiated steel samples in a hot cell (i.e. a shielded cell); the preparation, installation and commissioning of the equipment in a hot cell. The main part will focus on the presentation and discussion of the results up to 13 months leaching.

*This project is funded by Radioactive Waste Management and the European Union's Seventh Framework Programme for research, technological development and demonstration under grant agreement no. 604779, the CAST project.*